



R O S E B U R G

## SkyBlend™ Particleboard

Roseburg SkyBlend Particleboard is a No Added Urea Formaldehyde (NAUF) specified green particleboard panel.

It is EPP certified to be 100% recycled wood fiber particleboard and is now available as a FSC certified panel.

**NOW  
AVAILABLE  
FSC Certified**



R O S E B U R G  
**HYBRIDGREEN™  
PANELS**

Roseburg produces the most diverse line of green wood panel products in North America.

For more information or to order a Roseburg Green Products brochure go to [www.Roseburg.com](http://www.Roseburg.com)



R O S E B U R G

P.O. Box 1088  
Roseburg, OR 97470  
TF 800.245.1115  
FX 541.679.2543  
[www.Roseburg.com](http://www.Roseburg.com)

# SkyBlend Particleboard Panels

## Overview :

Roseburg SkyBlend Particleboard is a specified green particleboard panel. It is EPP certified to be 100% recycled wood fiber particleboard and has No Urea Formaldehyde added during the manufacturing process. The panel is a multi-layered substrate produced using a blend of wood fibers and particles that deliver the most desirable properties of each species. It is sanded to an extremely smooth, tight, and grainless surface on both sides. The core has a controlled distribution pattern of particles that creates the perfect dimensionally stable panel. Roseburg SkyBlend is engineered to the highest quality standards providing customers with the most desired properties. SkyBlend particleboard is available as raw board or can be specified as a core for mixed loads of Roseburg Duramine Melamine Panels, Hardwood Panels, Durashelf Melamine Shelving, Pre-Finished Light (Low) Basis Wt. Paper Overlaid Panels, Pre-Finished Vinyl Overlaid Panels, Pre-Finished UV Clear-Coated Panels and Pre-Finished Painted Panels. Available in industrial grade only.

## Specifications :

Specifications:

Density	47 - 50 lbs.
Length & Width Tolerances	+/- 0.080"
Thickness Tolerances:	
Panel Avg. from Specified	+/- 0.008"
Var. from Panel Average	+/- 0.004"
MOR	2103 psi
MOE	326,300 psi

IB	65 psi
Hardness	500 lbs.
Face Screw Holding	225 lbs.
Edge Screw Holding	202 lbs.
LE max. avg.	% 0.35

- Typical results of tests conducted using procedures outlined in ASTM D-1037.
- Sanded to 100 grit.
- SkyBlend Industrial Particleboard meets or exceeds the requirements of ANSI-1999 A208.1 Grade M2.

## AVAILABLE THICKNESSES, SIZES and UNIT PIECE COUNT

Dillard OR and Missoula MT

1/4"	49 x 97	100	11/16"	49 x 97	46
3/8"	49 x 97	80	3/4"	49 x 97, 61 x 97, 61 x 121	42
1/2"	49 x 97	64	1"	49 x 97	32
5/8"	49 x 97	50	1-1/8"	49 x 97, 61 x 97, 61 x 121	30

Southern Plants

1/4"	49 x 97	100	5/8"	49 x 97	46
1/2"	49 x 97	50	5/8"	61 x 97, 61 x 109	40
1/2"	61 x 97	60	3/4"	49 x 97	38
1/2"	61 x 109	48	3/4"	61 x 97, 61 x 109	32

- Custom sizes may be available subject to minimum order quantities and press utilization.
- 1/4" and 3/8" not available in FSC Certified.

## LEED Credits :

LEED CATEGORY/CREDIT	INTENT	REQUIREMENTS	POSSIBLE POINTS
<b>Materials and Resources MR Credit 4.1 Recycled Content:</b> <i>10% (post+ 1/2 pre-consumer)</i>	Increases the use of products that incorporate <b>recycled content</b> material	Sum of <b>recycled content</b> constitutes at least <b>10%</b> of materials in the project	1 point
<b>Materials and Resources MR Credit 4.2 Recycled Content:</b> <i>20% (post+ 1/2 pre-consumer)</i>	Increases the use of products that incorporate <b>recycled content</b> material	Sum of <b>recycled content</b> constitutes at least <b>20%</b> of materials in the project	1 point (in addition to MR credit 4.1)
<b>Indoor Environmental Quality EQ Credit 4.4: Low-Emitting Materials</b>	Improves indoor air quality	Wood products used shall contain <b>no added urea-formaldehyde resins</b>	1 point
<b>Materials and Resources MR 5.1 Regional Materials:</b> <i>10% Extracted, Processed &amp; Manufactured Regionally</i>	Increases the use of materials that are extracted and manufactured <b>within the project region</b>	A min. of <b>10%</b> of the combined value of building materials or products must be extracted, harvested, or recovered, as well as manufactured <b>within 500 miles</b> of the project	1 point
<b>Materials and Resources MR 5.2 Regional Materials:</b> <i>20% Extracted, Processed &amp; Manufactured Regionally</i>	Increases the use of materials that are extracted and manufactured <b>within the project region</b>	A min. of <b>20%</b> of the combined value of building materials or products must be extracted, harvested, or recovered, as well as manufactured <b>within 500 miles</b> of the project	1 point (in addition to MR credit 5.1)
<b>Materials and Resources MR Credit 7.0: Certified Wood</b> <i>FSC - Forest Stewardship Council</i> <b>NOTE: FSC Certified SkyBlend only</b>	Encourage environmentally responsible forest management	Use a minimum of 50% wood based materials and products, which are certified in accordance with the Forest Stewardship Council's (FSC) Principles and Criteria, for wood building components	1 point

## Key Advantages :

- FSC Certified SkyBlend now available.
- Core is tinted blue, making the product readily identifiable in the field.
- No Added Urea Formaldehyde (NAUF).
- Can contribute to achieving LEED credits.
- Made from 100% recycled fiber content (fiber basis).
- EPP - Environmentally Preferable Product.
- Meet or exceed ANSI standard A208.1-1999.
- Designed for laminating,
- High-quality smooth surface.
- Tight machinable edges.
- Excellent dimensional stability.

## Manufacturing Locations :

	SkyBlend Particleboard	SkyBlend FSC Particleboard
Dillard, OR	X	X
Missoula, MT	X	-
Southern Plants	X	-



Dillard, OR and Missoula, MT Sales: **TF** 800.245.1115 **FX** 541.679.2543  
 Southern Plants Sales: **TF** 866.387.2646 **FX** 678.474.1258

